

O2EII™ - Easy!

5 easy steps to a safe dive

Easy to use Ergonomically designed comfort grip handle with auto switch off after 10 minutes.

Easy to read Once you have taken your nitrox reading you can now freeze the display.

Easy to carry The Analox O2EII™ is fitted with a wrist lanyard.

Easy long life sensor change The sensor has a longer life and is easy for you to change

Easy to buy Buy your EII spares or accessories online at www.analox.net

What divers say ...

'I recently used the Analox O2EII in the Red Sea. I asked for a 32% mix but was actually given a 40%. The O2EII saved my life.'


Paul Norman – E-mail

'O2EII - Brilliant and easy to use. People keep borrowing mine then buying one themselves.'

Diver Forum 2004



Hold the O2EII™ in your left hand, press the button once to switch on. Auto switch off after 10 minutes



Adjust the calibration knob until the display reads the correct value, using the O2 compensation chart



Open the tank until you hear the nitrox gently hissing out



Hold the O2EII™ in your left hand and press the sample dome firmly against the cylinder outlet



Once you have a stable reading, press the on button to hold it. To cancel press the button once



If you are an instructor why not use this poster for training?

For extra copies email michelle@analox.net

Analox, sponsors of the BSAC Advanced Instructor Award



Dive into the future

The new Analox O2EII™ is designed to be a major step forward in diver safety. Building on the success of the original O2DII* the O2EII™ retains all the qualities of the original plus many new features.

- Comfort grip
- Freeze display
- Water resistant
- Lanyard
- Auto switch off

Its so easy to use, don't chance it check it



Take a direct reading from your nitrox tank

* One of the many Analox products approved by the US Navy.

Designed by the specialists

Analox have for over 20 years been designing and manufacturing analysers for military and commercial divers. We are breathing air specialists, let Analox look after the air you breathe. Check your nitrox with the O2EII™ every time you dive.

More of what divers say

'I asked for a 32% mix. Prior to my dive I checked the contents and actually had 36.4%. By having my own O2EII, I kept out of trouble.'

Bill Harrington – NEC Dive 2004

Specifications

Range:	0.1 - 100%	Resolution:	0.1% O2
Typical Accuracy:	+/- 1% of reading	Sensor warranty:	3 years graded
	+/- 0.2% of O2	Display:	4 digit LCD
Sensor life:	Upto 4 years	Dimensions:	Length 130mm
Power:	9 volt battery		Depth 55mm
Operating Temp:	-5 to +50°C		Width 70mm
Sensor response:	< 15 seconds to 90% of final reading.		Weight 225g
Electronics warranty:	3 years		

Analox has a policy of continuous improvement and we reserve the right to upgrade or change specifications without prior notice. V3 02/05



Copyright © Analox Ltd Feb 2005 Full technical specifications available upon request.

Shops and instructors please contact us for your special benefits package

Analox Sensor Technology Ltd
TS9 5JY UK
Tel: +44 1642 711400
Fax: +44 1642 713900
www.analox.net

ANALOX
looking after the air **you** breathe®

Don't chance it



check it
with the O2EII™